


PUNCH UNIT

PUNCH UNIT - INCLUDES PUNCH, DIE & DRAW		HOLE SIZE			CAPACITY STAINLESS STEEL		WEIGHT		DRIVER				DRAW STUD
Catalog No.	UPC No	Conduit and Pipe Size	ø inch	ø mm	GA	mm	LBS.	kg	1904	7804/7904	LS60*/ CLC60	7646/7625	
745R-1/2	30384	1/2"	7/8	22.5	16	1.5	.6	.27	x				30227
745H-1/2	29560	1/2"	7/8	22.5	10	3.5	.7	.32		x	x	x	29451
740H-1-7/32 Oil Tight	29563	-	1-7/32	30.5	10	3.5	1.2	.54		x	x	x	29452
 745H-3/4	12318	3/4"	1-3/32	28.3	10	3.5	1.26	.57				x	29452
 745H-1	12319	1"	1-11/32	34.6	10	3.5	1.51	.68				x	29452
 745H-1-1/4	12320	1-1/4"	1-11/16	43.2	10	3.5	1.96	.89				x	29452
 745H-1-1/2	12321	1-1/2"	1-15/16	49.6	10	3.5	2.49	1.13				x	29452
 745H-2	12322	2"	2-3/8	61.5	10	3.5	3.69	1.67				x	29452
 745M-15.2	12323	-	0.598	15.2	12	2.5	.98	.44				x	29451
 745M-16.2	12324	-	0.638	16.2	12	2.5	.97	.44				x	29451
 745M-18.6	12325	-	0.732	18.6	12	2.5	.98	.45				x	29451
 745M-20.4	12326	-	0.803	20.4	12	2.5	.96	.44				x	29451
 745M-25.4	12317	-	1.000	25.4	10	3.5	1.05	.48				x	29451
 745M-32.5	12327	-	1.280	32.5	10	3.5	1.53	.69				x	29452
 745M-37	12328	-	1.457	37	10	3.5	1.68	.76				x	29452
 745M-40.5	12329	-	1.595	40.5	10	3.5	1.83	.83				x	29452
 745M-47	12330	-	1.850	47	10	3.5	2.3	1.04				x	29452
 745M-50.8	12331	-	2.000	50.8	10	3.5	2.91	1.32				x	29452
 745M-54	12332	-	2.125	54	10	3.5	2.90	1.31				x	29452
 745M-60	12333	-	2.362	60	10	3.5	3.63	1.65				x	29452
 745M-64	12334	-	2.520	64	10	3.5	3.87	1.75				x	29452

* Battery-Powered or Corded Knockout Punch Driver