

Marine Products  
Molded Straight Adapters

**IP65**  
SUITABILITY



HBL21CM28



HBL21CM29



HBL31CM28



HBL31CM29



HBL61CM25

HBL61CM22  
HBL61CM22W



HBL61CM55  
HBL61CM54



HBL61CM59  
HBL61CM56



HBL61CM100



HBL105GF



HBL61CM71



HBL61CM72

**Molded Straight Adapters**

Description	Catalog Numbers
Permits use of 20A 125V Twist-Lock® locking type plug with 15 or 20A 125V straight blade receptacle. <b>IP20</b> SUITABILITY.	<b>HBL21CM28**</b>
Permits use of 15A or 20A 125V straight blade plug with 20A 125V Twist-Lock locking type receptacle. <b>IP20</b> SUITABILITY.	<b>HBL21CM29**</b>
Permits use of 30A 125V Twist-Lock® locking type plug with 15 or 20A 125V straight blade receptacle. <b>IP20</b> SUITABILITY.	<b>HBL31CM28</b>
Permits use of 15A or 20A 125V straight blade plug with 30A 125V Twist-Lock locking type receptacle. <b>IP20</b> SUITABILITY.	<b>HBL31CM29</b>
Permits use of 30A 125V cable set, #HBL61CM08, with 15 or 20A 125V straight blade receptacle. Anchor locking screw on plug when screwed down resists pullout of the cable set.	<b>HBL61CM22</b>
Same as #HBL61CM22, except white.	<b>HBL61CM22W</b>
Permits use of 30A 125V cable set, #HBL61CM08, with 20A 125V Twist-Lock® receptacle, #HBL23CM10.	<b>HBL61CM25</b>
Permits use of 50A 125V cable set, #HBL61CM53, with 15 or 20A 125V straight blade receptacle.	<b>HBL61CM54</b>
Permits use of 30A 125V cable set, #HBL61CM08, with 50A 125V Twist-Lock® receptacle, #HBL63CM70.	<b>HBL61CM55</b>
Permits use of 50A 125V cable set, #HBL61CM53, with 30A 125V Twist-Lock® receptacle, #HBL26CM10.	<b>HBL61CM56</b>
Permits use of 50A 125/250V Twist-Lock® locking type cable set, #HBL61CM52, with 50A 125/250V crow foot straight blade receptacle #HBL7962.	<b>HBL61CM59</b>
Permits use of 30A 125V cable set, #HBL61CM08, with 50A 125/250V Twist-Lock® receptacle, #HBL63CM69.	<b>HBL61CM71</b> <sup>^</sup>
Permits use of 50A 125V cable set, #HBL61CM53, with 50A 125/250V Twist-Lock® receptacle, #HBL63CM69.	<b>HBL61CM72</b> <sup>^</sup>
Permits use of 15A 125V 3 wire straight blade plug with 15 or 20A 125V 2 wire straight blade receptacle.	<b>HBL5273L</b> * **
Permits a 100 amp 125/250 volt cable set to plug into a single 50 amp 125/250 volt outlet.	<b>HBL61CM100</b>
Permits use of 15A straight blade plug with 30A 125V Twist-Lock® receptacle; with GFCI protection.	<b>HBL105GF</b>

Notes: \*Not shown.

\*\* UL listed.

Adapters do not provide overcurrent protection.

Adapters do not provide GFCI protection except HBL105GF.

<sup>^</sup>The male plug end (50A 125/250V) has a blade removed and the blade slot filled with epoxy Omitting the blade ensures achieving 125V safely.



# Marine Products Adapter Selection Guide

Boat/Cable Set Side

Power Center/Dock Side

**Catalog Numbers**

**Molded Straight Adapters**

**Connector Body (Female End)**

**Plug (Male End)**

15A 125V, 2P 3W Straight



**HBL105GF\***



30A 125V, 2P 3W Twist-Lock

30A 125V, 2P 3W Twist-Lock®



**HBL61CM22  
HBL61CM22W**



15A 125V, 2P 3W  
Straight Blade (lock type)

30A 125V, 2P 3W Twist-Lock



**HBL61CM25**



20A 125V, 2P 3W Twist-Lock

50A 125V, 2P 3W Twist-Lock



**HBL61CM54**



15A 125V, 2P 3W Straight Blade

30A 125V, 2P 3W Twist-Lock



**HBL61CM55**



50A 125V, 2P 3W Twist-Lock

50A 125V, 2P 3W Twist-Lock



**HBL61CM56**



30A 125V, 2P 3W Twist-Lock

50A 125/250V, 3P 4W Twist-Lock



**HBL61CM59**



50A 125/250V, 3P 4W Crow Foot

30A 125V, 2P 3W Twist-Lock



**HBL61CM71**



50A 125/250V, 3P 4W Twist-Lock

50A 125V, 2P 3W Twist-Lock



**HBL61CM72**



50A 125/250V, 3P 4W Twist-Lock

100A 125/250V, 3P 4W Pin/Sleeve



**HBL61CM100**



50A 125/250V, 3P 4W Twist-Lock

**Molded "Y" Adapters**

(2) 30A 125V, 2P 3W Twist-Lock



**HBL64CM54**



50A 125/250V, 3P 4W Twist-Lock

(2) 50A 125V, 2P 3W Twist-Lock



**HBL64CM55**



50A 125/250V, 3P 4W Twist-Lock

(2) 30A 125V, 2P 3W Twist-Lock



**HBL64CM56**



30A 125V, 2P 3W Twist-Lock

(2) 30A 125V, 2P 3W Twist-Lock



**HBL64CM57**



50A 125V, 2P 3W Twist-Lock

(2) 30A 125V, 2P 3W Twist-Lock



**HBL64CM59**



50A 125/250V, 3P 4W Crow Foot

**One Piece Adapters**

30A 125V, 2P 3W Twist-Lock



**HBL31CM28**



15A 125V, 2P 3W Straight Blade

15 or 20A 125V, 2P 3W Straight Blade



**HBL31CM29**



30A 125V, 2P 3W Twist-Lock

20A 125V, 2P 3W Twist-Lock



**HBL21CM28**



15A 125V, 2P 3W Straight Blade

15 or 20A 125V, 2P 3W Straight Blade



**HBL21CM29**



20A 125V, 2P 3W Twist-Lock

Note: See following two pages for photographs and descriptions.

\*Provides GFCI Protection

Dimensions in Inches (mm)

www.hubbell-wiring.com



V-25