


Rigid Conduit/IMC Fittings

Insulated Bushings — Iron/Zinc Plated



CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BI-901	1/2	1 1/32	1/2	1,000
BI-902	3/4	1 1/4	1/2	1,000
BI-903	1	1 1/16	9/16	500
BI-904	1 1/4	1 1/16	19/32	200
BI-905	1 1/2	2 1/64	5/8	100

UL File No. E-23018.




Insulated Grounding Bushings — Malleable Iron/Zinc Plated



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE CAPACITY	DIMENSIONS (IN.)		STD. CTN.
			A	B	
BG-801	1/2	—	1 1/32	1/2	500
BG-802	3/4	#14-#4 CU	1 1/4	1/2	500
BG-803	1	or 1 1/16	9/16	9/16	250
BG-804	1 1/4	#12-#4 AL	1 1/16	19/32	150
BG-805	1 1/2	—	2 1/64	5/8	150

UL File No. E-3060.

1/2"-2" Iron, 2 1/2"-4" Die-Cast Zinc.



Grounding Bushings Malleable Iron/Zinc Plated — Insulated with Aluminum Lug

- For copper or aluminum bare ground wire
- 105° C thermoplastic liners
- Heavy reinforced ribs



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG-801A	1/2	14 AWG	6 AWG	500
BG-802A	3/4	14 AWG	6 AWG	500
BG-803A	1	14 AWG	6 AWG	250
BG-804A	1 1/4	14 AWG	2 AWG	200
BG-805A	1 1/2	14 AWG	2 AWG	100
BG-806A	2	14 AWG	2 AWG	100

UL File No. E-3060.



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG-807A	2 1/2	14 AWG	2/0 AWG	50
BG-808A	3	14 AWG	2/0 AWG	50
BG-809A	3 1/2	14 AWG	2/0 AWG	10
BG-810A	4	14 AWG	2/0 AWG	10
BG-810B	4	6 AWG	250 kcmil	10

Reducing Bushings

- RB-121 thru RB-165 — Steel
- RB-175 thru RB-187 — Malleable iron (concrete tight), zinc plated



CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
RB-121	3/4-1/2	9/16	1/8	100
RB-131	1-1/2	7/8	1 1/8	50
RB-132	1-3/4	9/16	1 1/8	50
RB-141	1 1/4-1 1/2	11/16	1 1/8	50
RB-142	1 1/4-3/4	11/16	1 1/8	50
RB-143	1 1/4-1	11/16	1 1/8	50
RB-151	1 1/2-1 1/2	29/32	1 1/16	50
RB-152	1 1/2-3/4	29/32	1 1/16	50
RB-153	1 1/2-1	29/32	1 1/16	50
RB-154	1 1/2-1 1/4	29/32	1 1/16	50

UL File No. E-23018.

