



Representative Image

Catalog No. THHQL21125**Description: CIRCUIT BRK 22KA QL 2P 120/240V 125A****UPC No 783164087765****Home > Circuit Breakers > Residential Circuit Breakers > Q Line**

Q line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications. The QL breakers are plug-in versions of the Q Line used for connection to load centers and lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers are available in 1, 2, and 3 pole versions, can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications. 1125 Amps 125 A

Descriptors

| | |
|--------------|------------------|
| Category | Q Line |
| Product Line | Q-Line (Plug-In) |
| GO Schedule | R5 |

Specifications

| | |
|---------------------------------|------------------------|
| Interrupting Capacity Rating | 22 kAIC |
| Voltage | 120/240 V |
| Trip Style | Non-Interchangeable |
| Frame Type | Q-Line |
| Amperage | 125 A |
| System Voltage | 120 Vac 120/240 Vac |
| Poles | 2 |
| Trip Function | LI |
| Continuous Current Rated | Standard |
| 120 Vac Interrupting Rating | 22 KAIC |
| 120/240 Vac Interrupting Rating | 22 KAIC |
| Suitable for Reverse Feed | Yes |
| Long Time | Fixed |
| Instantaneous | Fixed |
| Protective Relays | No |
| Current Metering | No |
| Special Markings | HACR |
| GSA Compliance | Yes |

Classifications

| | |
|-----------|--------|
| UL File # | E11592 |
|-----------|--------|

Publications

| Title | Publication No. | Publication Type |
|---|----------------------|----------------------------------|
| Section 1 BuyLog: Load centers and circuit breakers | | |
| Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Q-Line Plug-In MCCB, 100A Frame 1-, 2-, or 3- Pole, Drawing | DET1023 | Application and Technical |
| 1-Page fully dimensioned outline drawing in .pdf format | 455C872-SH1 | Drawings-Outline and Dimensional |
| 125A 2P THHQL BREAKER 22K @ 120/240V FOR USE WITH 125A GE METER STACKS | | |
| 0 - 2P 70A 10K Breaker for 125A Sockets Outline Drawing | DEE-865 | Drawings-Outline and Dimensional |
| Q Line CAD Shell Files - 3D | | |
| CAD shell file in .stp format | AQ_THQL_2P_CAD_Shell | Drawings - CAD - 3D |

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.