

# PatchRunner™ 2 Vertical Cable Managers

**PANDUIT®**  
SPECIFICATION SHEET

## SPECIFICATIONS

The vertical cable manager shall consist of a metal backbone with cable management fingers that align with EIA rack spacing. The fingers shall be molded out of plastic and provide integral bend radius control throughout the entire length. The backbone shall have pass-through holes for front to back cabling, with the option to blank off with a plug. The manager shall accept a metal, hinged, push-to-close door that can open to the right or left. The door support brackets shall be integrated into the manager with no assembly required. The manager shall accept plastic slack management spools that can be repositioned as required. The vertical panel shall be able to manage all the cable on the rack without the aid of horizontal cable managers.



## TECHNICAL INFORMATION

Attributes:	Part Number	RU	Height in. (mm)	Width in. (mm)	Depth in. (mm)	
<b>6.5 foot managers and doors:</b>	<b>Dual-Sided</b>					
	<b>PR2VD0679</b>	42	78.9 (2003)	6.0 (152)	20.7 (526)	
	<b>PR2VD1279</b>			12.0 (305)		
	<b>Single-Sided</b>					
	<b>PR2VFD0679</b>	42	78.9 (2003)	6.0 (152)	12.0 (305)	
	<b>PR2VFD1279</b>			12.0 (305)		
<b>7 foot managers and doors:</b>	<b>Dual-Sided</b>					
	<b>PR2VD06^</b>	45	83.9 (2130)	6.0 (152)	20.7 (526)	
	<b>PR2VD08^</b>			8.0 (203)		
	<b>PR2VD10^</b>			10.0 (254)		
	<b>PR2VD12^</b>			12.0 (305)		
	<b>Single-Sided</b>					
	<b>PR2VFD06^</b>	45	83.9 (2130)	6.0 (152)	12.0 (305)	
	<b>PR2VFD08^</b>			8.0 (203)		
	<b>PR2VFD10^</b>			10.0 (254)		
	<b>PR2VFD12^</b>			12.0 (305)		
<b>8 foot managers and doors:</b>	<b>Dual-Sided</b>					
	<b>PR2VD0696^</b>	52	95.9 (2435)	6.0 (152)	20.7 (526)	
	<b>PR2VD0896^</b>			8.0 (203)		
	<b>PR2VD1096^</b>			10.0 (254)		
	<b>PR2VD1296^</b>			12.0 (305)		
	<b>Single-Sided</b>					
	<b>PR2VFD0696^</b>	52	95.9 (2435)	6.0 (152)	12.0 (305)	
	<b>PR2VFD0896^</b>			8.0 (203)		
	<b>PR2VFD1096^</b>			10.0 (254)		
	<b>PR2VFD1296^</b>			12.0 (305)		

<sup>^</sup>For part numbers in white, add "WH" to end of part number. Ex: PR2VD06WH or PR2VD0696WH

### Vertical Cable Managers with Doors

**Dual-sided with two doors:** PR2VD\*\*+^

**Dual-sided with one door:** PR2VSD\*\*+^

**Single-sided with one door:** PR2VFD\*\*+^

### Standard EIA Racks

**2-post aluminum rack with #12-24 threaded rails:** R2P+^

**4-post steel rack with #12-24 threaded rails:** R4P+^

**4-post steel rack with cage nut rails:** R4PCN+^

### Accessories

**7 in. front slack management spool:** PRSP7

**5 in. rear slack management spool:** PRSP5

**End panel:** PR2VEP+^

**Single-sided end panel:** PR2VFEP+

**Cable retainer:** WR5E-X

**Waterfall for use with 2-post, 4-post rack, and PR2V managers:** PR2VWF^

**Pass-through hole blanking plugs (kit of five plugs):** PR2VBPK

**Pass-through bend radius grommets (kit of five grommets):** PR2VGK

**15 RU finger section replacement kit:** PR2VRFK15^

**6 RU finger section replacement kit:** PR2VRFK6^

**Rear gate system kits (for use with single-sided managers):** PR2VRGSK\*\*

**PDU brackets:** PR2VPDUB

+Heights: 79 (6.5 ft.) or 96 (8 ft.)

<sup>^</sup>Colors other than black: WH (White)

<sup>\*\*</sup>Widths: 06 (6 in.), 08 (8 in.), 10 (10 in.) or 12 (12 in.).

# PatchRunner™ 2 Vertical Cable Managers

## KEY FEATURES AND BENEFITS

<b>Standards met:</b>	UL 2416, CSA C22.2
<b>Improved door function:</b>	“Push-to-close” door design allows for easy operation
<b>Dual-hinged doors are included:</b>	Doors ship with managers, simplifying ordering process with less packaging waste
<b>Integrated door brackets:</b>	No brackets to install; faster installation while reducing labor costs
<b>Curved fingers:</b>	Support cables as they transition to vertical pathway eliminating need for horizontal managers
<b>Individual fingers:</b>	Aligns with rack spaces to simplify cable routing changes
<b>Integral bend radius control:</b>	Maintains cable bend radius ensuring network performance and system reliability

## APPLICATIONS

PatchRunner 2 Vertical Cable Managers are designed to manage high-density networking equipment in up to half the area required by traditional cable management systems, and mount to Standard EIA Racks. Molded cable management fingers with integral bend radius control combine with angled patch panels to eliminate the need for horizontal cable managers. This frees up rack space for additional patch panels, active equipment, or cable pathways and reduces the number of racks that may be required for the network layout. Less square footage combined with fewer components results in significant cost savings. When used with connectivity solutions, patch cords, and racks the user receives a complete cable management solution, maximizing density while minimizing required network space.

## ENGINEERING DRAWINGS

- 1** R2P – 19 in. Standard EIA Rack  
19 in. x 3 in., 45 RU

**PatchRunner™ 2 Vertical Cable Managers and Doors**

- 2a** PR2VD06 – 6 in. wide  
**2b** PR2VD08 – 8 in. wide  
**2c** PR2VD12 – 12 in. wide

**Angled Modular Patch Panels**

- 3a** CPPLA48WBLY – 2 RU, 48-Port  
**3b** CPPA48HDWBLY – 1 RU, High Density 48-Port

**Cable Management Accessories**

- 4** PR2HF4 – Cable Manager, 4 RU  
**5** CMT4 – Trough, 4 RU  
**6** PR2VEP – End Panel  
**7** PR2VWF – Waterfall

