Gator® Plus Battery-Powered and Corded ACSR & Guy Wire Cutters



Battery-Powered and Corded Tool Features

- These cutters are designed specifically to cut steel cables and rods.
- The ram automatically retracts after the cut is complete to ready the tool for the next cut.
- The two-speed pump advances the ram rapidly to start the cut, reducing cycle time.
- Cutting head rotates 360° for making cuts in tight locations, and flips open to make mid-span cuts easy.
- U.S. Patents #6,206,663 and #6,065,326.

Battery-Powered Tool Features

- Includes one-hour battery charger, carrying case and two batteries.
- Choice of a 120 volt, 230 volt or 12 volt battery charger.

Corded Tool Features

- Operates directly from 120 volt 60Hz or 230 volt 50 Hz electrical outlets. No need to charge batteries or worry about running out of power.
- Equipped with 15 foot (5 m) cord. Can be used with extension cords.
- Includes carrying case.

CAT. NO.	UPC NO.		DESCRIPTION
ESG45GL11	10412		Battery-Powered ACSR Cable Cutter, 120 V charger
ESG45GL12	10413		Battery-Powered ACSR Cable Cutter, 12 V charger
ESG45GL22	10414		Battery-Powered ACSR Cable Cutter, 230 V charger
CSG45GL11	01382		Corded ACSR Cable Cutter, 120V
CSG45GL22	01383		Corded ACSR Cable Cutter, 230V
ESG45ESI	10398	R	Movable Blade
ESG45ES	10397	R	Fixed Blade
07063	07063	R	12V NIMH Battery
10411	10411	R	Carrying Case for ESG45GL
01598	01598	R	Carrying Case for CSG45GL
12274	12274	A	Carrying Strap
03046	03046	R	120V Charger
03048	03048	R	12V Charger
03047	03047	R	230V Charger

SPECIFICATIONS	
Capacity	
ACSR:	1590 kcmil (MCM), (Falcon 54/19)
Standard Guy Strand:	5/8" diameter (16 mm diameter)
EHS Guy Strand:	1/2" diameter (13 mm diameter)
Ground Rod:	5/8" diameter (16 mm diameter)
Rebar (schedule 60):	1/2" diameter (13 mm diameter)
Wire Rope:	5/8" diameter (16 mm diameter)
Copper and Aluminum Cable:	1500 kcmil (MCM) (800 mm^2)
Soft Steel Bolts:	5/8" diameter (16 mm diameter)
Length	15-1/2" (394 mm)
Height	12-1/2" (318 mm)
Weight	12.8 lbs. (5.8 kg)
Battery	12V, 2.6 Ah, NIMH
Battery Charge Time	– 1 hour

Hydraulic ACSR Cable Cutter



- Hydraulic cutter takes the effort out of cutting tough cables.
- Flip-open head provides strength while making it easy to cut long lengths.
- Head rotates 180°.
- Thumb release lever for quick blade retraction.

CAT. NO.	UPC NO.		DESCRIPTION
HK520	08031		Hydraulic ACSR Cable Cutter
00336	00336	R	Cutter Blade
00301	00301	R	Fixed Cutter Head

SPECIFICATIONS	
Capacity	ACSR: 336.4 kcmil (MCM) Standard Guy Wire, Ground Rod: 1/2" (13 mm) Soft Steel Bolts: 11/16" (17 mm) Wire Rope: 3/4" (19 mm) Rebar: 7/16" dia. (Schedule 60)
Length	14.5" (368 mm)
Weight	5.7 lbs. (2.6 kg)

USA Tel: 800.435.0786 Fax: 800.451.2632
Canada Tel: 800.435.0786 Fax: 800.524.2853
International Tel: +1.815.397.7070 Fax: +1.815.397.9247

R = REPLACEMENT PART A = ACCESSORY