LITHONIA LIGHTING®

Catalog Number	
Notes	
Type	

FEATURES & SPECIFICATIONS

INTENDED USE

Provides years of maintenance-free illumination for indoor or outdoor use in residential & commercial applications.

CONSTRUCTION

Cast-aluminum housing with corrosion-resistant paint in an industrial grey finish.

Sealed gasket protects against moisture and dust.

OPTICS

4000K CCT LEDs.

Frosted glass diffuser provides even light distribution.

LUMEN MAINTENANCE

LEDs will deliver 70% of their initial lumens at 50,000 hour average LED life. See Lighting Facts label on page 2 for performance details.

ELECTRICAL

MVOLT driver operates on any line voltage from 120-277V

Operating temperature -40ºC to 40ºC.

4kV surge protection standard.

INSTALLATION

Mounts to ceiling or wall with surface mount junction box (included).

LISTINGS

UL Listed to U.S. and Canadian safety standards for wet locations.

Tested in accordance with IESNA LM-79 and LM-80 standards.

WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Full warranty terms located at www.AcuityBrands.com/CustomerResources/Terms_and_Conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications are subject to change without notice.

Outdoor General Purpose


OLVTCM & OLVTWM



LED VAPORTIGHT

Specifications

All dimensions are inches (centimeters)



ORDERING INFORMATION For shortest lead times, configure products using **bolded options**. **Example:** OLVTCM


Series	Color temperature	Voltage	Finish
OLVTCM Ceiling MT **OLVTWM** Wall MT	**(blank)** 4000K	**(blank)** MVOLT (120V-277V)	**(blank)** Grey


Series	System Wattange	Lumens
OLVTCM	15W	600
OLVTWM	15W	600

PHOTOMETRICS


To see complete photometric reports or download .ies files for this product,visit Lithonia Lighting's Outdoor LED homepage
Tested in accordance with IESNA LM-79 and LM-80 standards.


OLVTCM





OLVTWM





© 2012-2022 Acuity Brands Lighting, Inc. All rights reserved.