

K2B

1 Conduit Hanger W/Bolt PG

UPC:	78461011002
UNSPSC:	31162306
Standard Qty:	100
Master Carton Qty:	100
Country of Origin:	USA

1" Conduit Hanger with Bolt, 1" EMT or 1" RMC/IMC, 1/4-20 Keyholed - No nut required, Pre-Galvanized, Box/100



Product Attributes

Brand Name	Minerallac
Sub Brand	Minerallac Traditional
Type	Conduit Hanger
Application	Electrical Conduit
Special Features	Heavy-duty gauge material. Designed for use on loads too heavy to be supported by 1-hole straps.
Material	Steel
Finish	Pre-Galvanized
Mounting Holes	1
Mounting	Component, Wood, Steel, Concrete
Mounting Holes O.C.	1/4"
Number of Holes	3
Size	2.40" x 1.45" x 0.75"
Color	Silver
Width	1.450"
Length	0.750"
Load Capacity	60
Included	Bolt with Plastic Retaining Washer
Material Of Construction	Low-Carbon Cold-Rolled Steel
Rod Size	0.250"
Installation	Bolt On
Hanger Type	Conduit Hanger
Pipe Size	Fits 1" Rigid/IMC and EMT.
Height	2.400"

Compliance Information

Buy America Act Compliant:	No
Buy American Act Compliant:	Yes
RoHS Compliant:	Yes
UL Compliant:	Yes
UL Code:	9N38

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293
 Fax: 800-824-8942
www.minerallac.com

K2B

1 Conduit Hanger W/Bolt PG

UPC: 78461011002

UNSPSC: 31162306

Standard Qty: 100

Master Carton Qty: 100

Country of Origin: USA

1" Conduit Hanger with Bolt, 1" EMT or 1" RMC/IMC, 1/4-20
Keyholed - No nut required, Pre-Galvanized, Box/100



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.