

Cable, Cord and Hose Reels

Industrial Cord Reels



HBL45123TL20



HBL45123C



HBL45123TL20



HBL45123R



HBL45123GF15



HBL50163IN



HBL50162FL



HBL340PB

Industrial Power Cord Reels

Cord End	NEMA Style	Cable Feet (m)	Volts AC	Cable Type	Amps	Weight Lbs. (kg)	Catalog Number
HBL5269C Connector.	5-15R	45 (13.7)	125	12/3 SJO	15	23 (10.4)	HBL45123C
HBL5369C Connector.	5-20R	45 (13.7)	125	12/3 SJO	20	23 (10.4)	HBL45123C20
HBL2313 Connector.	L5-20R	45 (13.7)	125	12/3 SJO	20	28 (12.7)	HBL45123TL20
HBL2313 Connector (white reel housing).	L5-20R	45 (13.7)	125	12/3 SJO	20	28 (12.7)	HBL45123TL20W
Portable Outlet Box with (1) gray duplex receptacle.	5-15R	45 (13.7)	125	12/3 SJO	15	29 (13.2)	HBL45123R
	5-20R	45 (13.7)	125	12/3 SJO	20	29 (13.2)	HBL45123R20
Portable Outlet Box with (1) ground fault protected gray duplex receptacle.	5-15R	45 (13.7)	125	12/3 SJO	15	29 (13.2)	HBL45123GF15
	5-20R	45 (13.7)	125	12/3 SJO	20	29 (13.2)	HBL45123GF20
Pivot Base 330° Rotation fits all industrial models.	—	—	—	—	—	5 (2.3)	HBL340PB
Replacement stop.	—	—	—	—	—	.2 (.09)	HBL12BS

Notes: 15 Amp: Supplied with 5 ft. power supply cord with **HBL5266C**, 15A straight blade plug.

20 Amp: Supplied with 5 ft. power supply cord with **HBL5366C**, 20A straight blade plug.

Ground fault protected reels supplied with (1) **GFM20** and (1) **HBLP26FS**.


Industrial Light Cord Reels

Cord End	Watts (Max)	Cable Feet (m)	Volts AC	Cable Type	Amps	Weight Lbs. (kg)	Catalog Number
Incandescent Hand Lamp.	100	50 (15.2)	125	16/3	0.8	21 (9.5)	HBL50163IN
Fluorescent Hand Lamp.	13	50 (15.2)	120	16/2	0.3	21 (9.5)	HBL50162FL
Pivot Base 330° Rotation fits all industrial models.	—	—	—	—	—	5 (2.3)	HBL340PB
Replacement stop.	—	—	—	—	—	.2 (.09)	HBL16BS


Note: Supplied with 5 ft. power supply cord with **HBL5266C**, 15A straight blade plug.

Three Mounting Positions


Wall mount



Ceiling mount





Bench mount



Dimensions

Inch (mm)	A	B	C	D	E	F
	13.00"	12.38"	8.00"	2.50"	9.75"	1.25"
	(330)	(314)	(203)	(64)	(248)	(32)



All models have four 5/16" diameter mounting holes.

Listings/Certifications

UL 355
CSA C22.2 No. 21.

Environment

Dry, indoor, non-hazardous locations.