



# Energy Advantage IR PAR38

## Energy Advantage IR 70PAR38/IRC+/FL25 120V

Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

### Product data

General Information	
Base	E26 [ Single Contact Medium Screw]
Operating Position	Universal [ Universal]
Main Application	Outdoor (OD)
Gas Filling	GAS
Life with 3 Hour Per Day Use	3.8 a
Light Technical	
Beam Angle (Nom)	25 °
Initial lumen (Max)	1500 lm
Initial lumen (Nom)	1415 lm
Luminous Intensity (Nom)	6170 cd
Beam Description	Flood [ Flood]
Correlated Color Temperature (Max)	2860 K
Correlated Color Temperature (Nom)	2820 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	70 W
Voltage (Nom)	120 V
Mechanical and Housing	
Bulb Finish	Clear (CL)

Cap-Base Information	Brass [ Brass Cap]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [ Axial]

### Approval and Application


Estimated Energy Cost Per Year at 120V	8.43 \$
Estimated Energy Cost Per Year	8.43 \$

### Product Data

Order product name	Energy Advantage IR 70PAR38/IRC+/FL25 120V
EAN/UPC - Product	046677138622
Order code	138628
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	924757119670
Net Weight (Piece)	355.000 g

# Energy Advantage IR PAR38

## Dimensional drawing



Product	D	C (max)
Energy Advantage IR 70PAR38/IRC+/FL25 120V	4.75 in	5.313 in

PAR38 IRC 70W E26/Brass 120V FL 25D CC-8

